



## CO2 Fire Extinguisher-18

CO2 Fire Extinguishers-18 are an effective tool for putting out fires involving flammable liquids and Product code: 1815105100 molten materials (class B) as well as burning electrical equipment that is still under voltage up to 1000V (class C) where oxygen is involved. The extinguishing agent used in these fire extinguishers is carbon dioxide (CO2). The CO2 gas is expelled from the extinguisher at high pressure, creating a sharp expansion of the gas volume and emitting cold to cool down the burning material.

These fire extinguishers can be used within a temperature range of -20°C to +50°C, making them suitable for use in a variety of environments. They also have a long service life, with an operational time of up to 10 years.

It's important to note that these fire extinguishers require annual maintenance to ensure that they are in good working condition. This maintenance should be carried out by a professional at the customer's enterprise to ensure that the extinguisher is ready to use in case of an emergency.

## **Specifications:**

- · Volume of shell 25 l;
- · CO2 content 18 kg;
- · Fire-killing capability 70B;
- · Fire extinguisher full weight, not more than - 90 kg;
- · Minimal jet lenth 4 m;
- · Minimal discharge time 20 sec;
- · Length 1450 mm;
- · Height 800 mm;
- · Width 500 mm;
- · Diameter 219 mm;



email: welcome@markogroup.com